

**Amendments to the Claims:**

1-3. (canceled)

4. (currently amended) ~~The method as recited in Claim 1, further comprising the step of:~~

A method for providing self-provisioning of VoIP telephony service to a subscriber of the VoIP telephony service, the method comprising the computer-implemented steps of:

receiving a first notify command from ~~the~~ an un-provisioned residential gateway that is associated with the subscriber, wherein the first notify command is sent in response to a telephone receiver connected to the residential gateway going off-hook; ~~and~~

instructing the residential gateway to collect a provisioning access number;

instructing, via a call signaling command, the residential gateway to collect a subscriber numeric identity that uniquely identifies the subscriber;

instructing, via a call signaling command, the residential gateway to collect a Personal Identification Number (PIN) information that is associated with the subscriber;

receiving and verifying the subscriber numeric identity and Personal Identification Number (PIN) information;

assigning an IP address that is associated with one or more Media Gateway Control

Protocol (MGCP) messages that are sent by the residential gateway as a

residential gateway IP address for the residential gateway; and

using the residential gateway IP address to provision the residential gateway that is associated with the subscriber.

5. (original) The method as recited in Claim 4, wherein instructing the residential gateway to collect a provisioning access number further comprises sending a MGCP notification request with a first digit map associated with the provisioning access number.
6. (currently amended) The method as recited in Claim ~~[[1]]~~8, further comprising the steps of:  
  
receiving and storing a provisioning access number from the residential gateway; and  
  
wherein instructing the residential gateway to collect a subscriber numeric identity includes instructing the residential gateway to create a first VoIP connection between the residential gateway and an announcement server for sending a first VoIP message from the announcement server to the subscriber via the residential gateway in order to collect the subscriber numeric identity.
7. (original) The method as recited in Claim 6, further comprising the step of:  
  
receiving and storing the subscriber numeric identity from the residential gateway; and  
  
instructing the residential gateway to delete the first VoIP connection.
8. (currently amended) ~~The method as recited in Claim 1, further comprising the step of:~~  
  
A method for providing self-provisioning of VoIP telephony service to a subscriber of the VoIP telephony service, the method comprising the computer-implemented steps of:

instructing, via a call signaling command, the residential gateway to collect a  
subscriber numeric identity that uniquely identifies the subscriber;  
instructing, via a call signaling command, the residential gateway to collect a Personal  
Identification Number (PIN) information that is associated with the subscriber;  
wherein instructing the residential gateway to collect a Personal Identification Number  
includes  
after the residential gateway deletes a first VoIP connection, instructing the  
residential gateway to create a second VoIP connection between the  
residential gateway and an announcement server for sending a second  
VoIP message from the announcement server to the subscriber via the  
residential gateway in order to collect the Personal Identification  
Number (PIN) information from the subscriber;  
receiving and verifying the subscriber numeric identity and Personal Identification  
Number (PIN) information;  
assigning an IP address that is associated with one or more Media Gateway Control  
Protocol (MGCP) messages that are sent by the residential gateway as a  
residential gateway IP address for the residential gateway; and  
using the residential gateway IP address to provision the residential gateway that is  
associated with the subscriber.

9. (original) The method as recited in Claim 8, further comprising the step of:  
receiving and storing the Personal Identification Number (PIN) information; and  
instructing the residential gateway to delete the second VoIP connection.

10-20. (canceled)

21. (currently amended) ~~The method as recited in Claim 1,~~ A method for providing self-provisioning of VoIP telephony service to a subscriber of the VoIP telephony service, the method comprising the computer-implemented steps of:  
instructing, via a call signaling command, the residential gateway to collect a  
subscriber numeric identity that uniquely identifies the subscriber;  
instructing, via a call signaling command, the residential gateway to collect a Personal  
Identification Number (PIN) information that is associated with the subscriber;  
receiving and verifying the subscriber numeric identity and Personal Identification  
Number (PIN) information;  
assigning an IP address that is associated with one or more Media Gateway Control  
Protocol (MGCP) messages that are sent by the residential gateway as a  
residential gateway IP address for the residential gateway; and  
using the residential gateway IP address to provision the residential gateway that is  
associated with the subscriber;  
wherein ~~the step of~~ using the residential gateway IP address to provision the  
residential gateway further comprises ~~the step of~~ rebooting the residential  
gateway remotely by a self-provisioning system call agent of a self-  
provisioning system that is associated with a provider of the VoIP telephony  
service.

22. (currently amended) ~~The method as recited in Claim 1,~~ A method for providing self-provisioning of VoIP telephony service to a subscriber of the VoIP telephony service, the method comprising the computer-implemented steps of:  
~~wherein the~~ a residential gateway requests ~~requesting~~ a location of one or more Domain Name System (DNS) server, a limited-access IP address, and a Media Gateway Control Protocol (MGCP) endpoint name of a self-provisioning system call agent of a self-provisioning system that is associated with the provider of the VoIP telephony service;  
instructing, via a call signaling command, the residential gateway to collect a subscriber numeric identity that uniquely identifies the subscriber;  
instructing, via a call signaling command, the residential gateway to collect a Personal Identification Number (PIN) information that is associated with the subscriber;  
receiving and verifying the subscriber numeric identity and Personal Identification Number (PIN) information;  
assigning an IP address that is associated with one or more Media Gateway Control Protocol (MGCP) messages that are sent by the residential gateway as a residential gateway IP address for the residential gateway; and  
using the residential gateway IP address to provision the residential gateway that is associated with the subscriber.
23. (currently amended) ~~The method as recited in Claim 1, further comprising~~ A method for providing self-provisioning of VoIP telephony service to a subscriber of the VoIP telephony service, the method comprising the computer-implemented steps of:

using a subscriber registration center that is associated with a provider of the VoIP telephony service wherein the subscriber registration center performs the steps of:

- offering ~~to the residential~~ to a residential gateway a limited access IP address;
- offering to the residential gateway a location of one or more Domain Name System (DNS) servers;
- offering to the residential gateway a Media Gateway Control Protocol (MGCP) endpoint name of a self-provisioning system call agent of a self-provisioning system that is associated with the provider of the VoIP telephony service;

instructing, via a call signaling command, the residential gateway to collect a subscriber numeric identity that uniquely identifies the subscriber;

instructing, via a call signaling command, the residential gateway to collect a Personal Identification Number (PIN) information that is associated with the subscriber;

receiving and verifying the subscriber numeric identity and Personal Identification Number (PIN) information;

assigning an IP address that is associated with one or more Media Gateway Control Protocol (MGCP) messages that are sent by the residential gateway as a residential gateway IP address for the residential gateway; and

using the residential gateway IP address to provision the residential gateway that is associated with the subscriber.

24. (original) The method as recited in Claim 23, wherein the step of offering to the residential gateway a limited access IP address is performed through a Dynamic Host Configuration Protocol (DHCP) server.
25. (original) The method as recited in Claim 23, wherein the step of offering to the residential gateway a location of one or more Domain Name System (DNS) servers is performed through a Dynamic Host Configuration Protocol (DHCP) server.
26. (original) The method as recited in Claim 23, wherein the step of offering to the residential gateway a Media Gateway Control Protocol (MGCP) endpoint name of a self-provisioning system call agent of a self-provisioning system that is associated with the provider of the VoIP telephony service is performed through a Dynamic Host Configuration Protocol (DHCP) server.
27. (currently amended) The method as recited in Claim 23, wherein [[the]] a protocol server directs a provisioned residential gateway to a standard call agent that is associated with the provider of the VoIP telephony service to enable VoIP calls and services.
28. (currently amended) A method for providing self-provisioning of VoIP telephony to a subscriber of a VoIP telephony service, the method comprising the computer-implemented steps of:  
  
receiving a first notify command from a residential gateway that is associated with the subscriber and that has not been provisioned, wherein the first notify command

is sent in response to a lifting of a telephone receiver connected to the residential gateway;

after receiving the first notify command from the residential gateway, instructing the residential gateway to collect a provisioning access number;

receiving a second notify command from the residential gateway, wherein the second notify command is sent with the provisioning access number;

receiving and storing the provisioning access number;

after receiving the second notify command, instructing the residential gateway to create a first VoIP connection between the residential gateway and an announcement server for sending a first VoIP message from the announcement server to the subscriber in order to collect a subscriber numeric identity that uniquely identifies the subscriber;

instructing the residential gateway to collect the subscriber numeric identity that is allocated to the subscriber;

receiving a third notify command from the residential gateway, wherein the third notify command is sent with the subscriber numeric identity;

receiving and storing the subscriber numeric identity;

after receiving the third notify command from the residential gateway, instructing the residential gateway to delete the first VoIP connection;

after the residential gateway deletes the first VoIP connection, instructing the residential gateway to create a second VoIP connection between the residential gateway and the announcement server for sending a second VoIP message from the announcement server to the subscriber in order to collect a Personal Identification Number (PIN) information from the subscriber;



instructing the residential gateway to collect the Personal Identification Number (PIN) information that is associated with the subscriber;

receiving a fourth notify command from the residential gateway, wherein the fourth notify command is sent with the Personal Identification Number (PIN) information;

receiving and storing the Personal Identification Number (PIN) information;

after receiving the fourth notify command from the residential gateway, instructing the residential gateway to delete the second VoIP connection;

verifying the subscriber numeric identity and PIN information;

using a source IP address that is associated with one or more Media Gateway Control Protocol (MGCP) messages that are sent by the residential gateway as a residential gateway IP address for the residential gateway; and

using the residential gateway IP address to provision the residential gateway by performing the steps of:

enabling a Dynamic Host Configuration Protocol-centric (DHCP-centric) protocol server to query a Dynamic Host Configuration Protocol (DHCP) server for a mapping from the residential gateway IP address to a MAC address associated with the residential gateway;

enabling the DHCP-centric protocol server to configure the DHCP server to offer a long-term IP address to the residential gateway; and

enabling the DHCP-centric protocol server to configure the DHCP server to associate a Domain Name System (DNS) hostname that is based on the subscriber numeric identity with the MAC address of the residential gateway.

29. (currently amended) A computer-readable medium carrying one or more sequences of instructions for providing self-provisioning of VoIP telephony to a subscriber of VoIP telephony service, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:
- instructing, via a call signaling command, an un-provisioned residential gateway that is associated with the subscriber to collect an subscriber numeric identity that uniquely identifies the subscriber;
- instructing, via a call signaling command, the residential gateway to collect a Personal Identification Number (PIN) information that is associated with the subscriber;
- receiving and verifying the subscriber numeric identity and Personal Identification Number (PIN) information;
- assigning an IP address that is associated with one or more Media Gateway Control Protocol (MGCP) messages that are sent by the residential gateway as a residential gateway IP address for the residential gateway; [[and]]
- using the residential gateway IP address to provision the residential gateway that is associated with the subscriber; and
- wherein using the residential gateway IP address to provision the residential gateway further comprises rebooting the residential gateway remotely by a self-provisioning system call agent of a self-provisioning system that is associated with a provider of the VoIP telephony service.
30. (currently amended) An apparatus for providing self-provisioning of VoIP telephony to a subscriber of a VoIP telephony service, which apparatus, comprising:

means for instructing, via a call signaling command, an un-provisioned residential gateway that is associated with the subscriber to collect an subscriber numeric identity that uniquely identifies the subscriber;

means for instructing, via a call signaling command, the residential gateway to collect a Personal Identification Number (PIN) information that is associated with the subscriber;

means for receiving and verifying the subscriber numeric identity and Personal Identification Number (PIN) information;

means for assigning an IP address that is associated with one or more Media Gateway Control Protocol (MGCP) messages that are sent by the residential gateway as a residential gateway IP address for the residential gateway; [[and]]

means for using the residential gateway IP address to provision the residential gateway that is associated with the subscriber; and

wherein the means for using the residential gateway IP address to provision the residential gateway further comprises means for rebooting the residential gateway remotely by a self-provisioning system call agent of a self-provisioning system that is associated with a provider of the VoIP telephony service.

31. (currently amended) An apparatus for providing self-provisioning of VoIP telephony to a subscriber of a VoIP telephony service, which apparatus, comprising:
- a network interface that is coupled to the data network for receiving one or more packet flows therefrom;
- a processor;

one or more stored sequences of instructions which, when executed by the processor,  
cause the processor to carry out the steps of:  
instructing, via a call signaling command, an un-provisioned residential gateway that  
is associated with the subscriber to collect a subscriber numeric identity of the  
subscriber;  
instructing, via a call signaling command, the residential gateway to collect a Personal  
Identification Number (PIN) information that is associated with the subscriber;  
receiving and verifying the subscriber numeric identity and Personal Identification  
Number (PIN) information;  
assigning an IP address that is associated with one or more Media Gateway Control  
Protocol (MGCP) messages that are sent by the residential gateway as a  
residential gateway IP address for the residential gateway; [[and]]  
using the residential gateway IP address to provision the residential gateway that is  
associated with the subscriber; and  
wherein using the residential gateway IP address to provision the residential gateway  
further comprises rebooting the residential gateway remotely by a self-  
provisioning system call agent of a self-provisioning system that is associated  
with a provider of the VoIP telephony service.